Simple R



Only 2" Thick!



CONTROL FEATURES

- 3 or 7-channel DMX-512 slim LED PAR can
- Operating modes:
 - 3-channel: RGB control
 - 7-channel: RGB, macros, run/strobe speed, automatic/sound, dimmer
- Static colors and RGB color mixing with or without DMX controller
- Built-in automated programs via master/slave or DMX with variable speed
- Built-in sound activated programs via master/slave or DMX
- Pulse effect with adjustable speed

ADDITIONAL FEATURES

- Low-profile lights are 2.2in deep
- Additional power output: max 46 units @ 120V
- Double-bracket yoke doubles as floor stand

SPECIFICATIONS

- Beam angle: 21°
- Field angle: 32°
- Lux: 1,290 @ 1m
- Light Source: 108 (36 red, 36 green, 36 blue) LEDs
- Power and current: 120V, 60Hz: 8W, 0.2A operating, 0.2A inrush
- Power and current: 230V, 50Hz: 12W, 0.1A operating, 0.2A inrush
- AC power: Autoswitching 100V-240V 50/60Hz
- Weight: 2.7lbs (1.2kg)
- Size: 8.8in x 7.3in x 7in

223mm x 184mm x 178mm





www.chauvetlighting.com info@chauvetlighting.com t: 954.929.1115 3000 North 29th Court

