

CONTROL FEATURES

- 3 or 7-channel DMX-512 LED PAR can
- Operating modes: 3-channel: RGB control
7-channel: RGB, macros, run/strobe speed, automatic/sound, dimmer
- Static colors and RGB color mixing with or without DMX controller
- Built-in automated programs via master/slave or DMX with variable speed
- Built-in sound activated programs via master/slave or DMX
- Pulse effect with adjustable speed

ADDITIONAL FEATURES

- Additional power output: max 25 units @ 120V
- Double-bracket yoke doubles as floor stand

SPECIFICATIONS

- Beam angle: 20°, Field angle: 32°, Lux: 2,020 @ 1m
- Light Source: 183 (61 red, 61 green, 61 blue) 10mm LEDs
- Power and current: 120V, 60Hz: 17W, 0.3A operating, 0.2A inrush
- AC power: Autoswitching 100V-240V 50/60Hz
- Weight: 2.9lbs (1.3kg)
- Size: 8.4in x 8.9in x 12.2in, 213mm x 225mm x 309mm



LEDrain™ 64C

CONTROL FEATURES

- 3 or 7-channel DMX-512 LED PAR can
- Operating modes: 3-channel: RGB control
7-channel: RGB, macros, run/strobe speed, automatic/sound, dimmer
- Static colors and RGB color mixing with or without DMX controller
- Built-in automated programs via master/slave or DMX with variable speed
- Built-in sound activated programs via master/slave or DMX
- Pulse effect with adjustable speed

ADDITIONAL FEATURES

- Additional power output: max 37 units @ 120V
- Double-bracket yoke doubles as floor stand

SPECIFICATIONS

- Beam angle: 20°, Field angle: 32°, Lux: 1,390 @ 1m
- Light Source: 108 (36 red, 36 green, 36 blue) 10mm LEDs
- Power and current: 120V, 60Hz: 8W, 0.2A operating, 0.2A inrush
- AC power: Autoswitching 100V-240V 50/60Hz
- Weight: 2.6lbs (1.2kg)
- Size: 7.6in x 8.2in x 11.9in, 194mm x 208mm x 302mm



LEDrain™ 56C

CONTROL FEATURES

- 3 or 7-channel DMX-512 LED PAR can
- Operating modes: 3-channel: RGB control
7-channel: RGB, macros, run/strobe speed, automatic/sound, dimmer
- Static colors and RGB color mixing with or without DMX controller
- Built-in automated programs via master/slave or DMX with variable speed
- Built-in sound activated programs via master/slave or DMX
- Pulse effect with adjustable speed

ADDITIONAL FEATURES

- Additional power output: max 37 units @ 120V
- Double-bracket yoke doubles as floor stand

SPECIFICATIONS

- Beam angle: 15°, Field angle: 23° Lux: 1,033 @ 1m
- Light Source: 75 (25 red, 25 green, 25 blue) 10mm LEDs
- Power and current: 120V, 60Hz: 10W, 0.2A operating, 0.2A inrush
- AC power: Autoswitching 100V-240V 50/60Hz
- Weight: 2.8lbs (1.2kg)
- Size: 6.2in x 7.4in x 11.2in, 157mm x 188mm x 284mm



LEDrain™ 38C

www.chauvetlighting.com
info@chauvetlighting.com
t: 954.929.1115
3000 North 29th Court
Hollywood, FL 33020

CHAUVET
Value • Innovation • Performance