

Legend™ 4500



CONTROL FEATURES

- 10 or 14-channel DMX-512 LED moving yoke color wash
- Pan: 540° / tilt: 270°
- RGBW color mixing with or without DMX controller
- Vector speed channel for RGBW color mixing
- Variable electronic strobe
- Variable electronic dimmer (0 – 100%)
- Remote fixture reset and vector speed channel
- 255 user-programmable steps without DMX controller
- Color temperature presets (3,200 K - 10,000 K)
- Move-in-black for pan/tilt
- Adjustable fan speed

ADDITIONAL FEATURES

- 3-pin and 5-pin DMX connections
- PowerCon® connector
- User-selectable pan/tilt ranges
- Automatic pan/tilt correction
- Reset to factory settings option
- User-selectable basic or advanced operating modes
- LCD display with password protection

OPTIONS

- Optical systems available: 30° (CL20X30)

SPECIFICATIONS

- Installed optics: 15°
 - Beam angle: 10°
 - Field angle: 22°
 - Lux: 14,850 @ 2 m
- Light source: 54 x 2 ~ 3 W LEDs, 50,000 hrs
 - (14 x 700 mA red, 14 x 1,000 mA green, 14 x 1,000 mA blue, 12 x 1,000 mA white)
- Power and current: 120 V, 60 Hz; 221 W, 1.85 A (operating), 0.6 A (inrush), PF 0.99
 - 230 V, 50 Hz; 213 W, 0.99 A (operating), 1.8 A (inrush), PF 0.94
- AC power: Auto-ranging 100 V ~ 240 V 50/60 Hz
- Power input cable: 60 in (1,524 mm)
- Weight: 37 lbs / 16.8 kg
- Size: 15.4 x 12.6 x 16.9 in / 390 x 320 x 430 mm



www.chauvetlighting.com
info@chauvetlighting.com
t: 954.929.1115
3000 North 29th Court
Hollywood, FL 33020

CHAUVET
Value • Innovation • Performance