


SCHEDA TECNICA / TECHNICAL SHEET

125-2

2 x 250W PA Amplifier







Designed for piped systems, it is able to provide an RMS power of 2x125W with both 4 Ohm and 70V/100V output. Each channel has independent balanced XLR input and independent volume control.

A selector allows you to choose the mode of use between MONO and DUAL. A filter can be operated for cutting high/low.

Each channel has independent LED indicators for signal, 4 Ohm, 70V, 100V and Pro.

Matrix	No
RMS power	2 x 125W
4 Ohm max power	500 W
8 Ohm max power	250W
Input impedance	70V, 100V
Impedance	4 Ohms
Multi zone	No
Phantom Key	No
Cooling fan	1 fan
Rack space	2U
Input connectors	XLR
Output connectors	screw terminal
Line inputs	2
Mic inputs	0
Constant voltage	70 - 100V compatible
S/N ratio	>95dB
Frequency response	L/H cut off 20Hz - 20 KHz
Color	black
Weight	6,9
Product dimensions	435 x 88 x 340mm





Karma Italiana srl si impegna affinchè le informazioni contenute in questa scheda siano le più precise possibili. Allo scopo di migliorare i propri prodotti, Karma Italiana si riserva il diritto di apportare modifiche ai propri prodotti senza alcun preavviso. Tutti i prodotti Karma sono conformi alle normative vigenti dell'Unione Europea.



