

SCHEDA TECNICA / TECHNICAL SHEET

PAA 60DMB

60W amplifier with DAB



























Amplifier intended for PA system installations. It includes a Mp3 module offering the possibility to play tracks from USB/SD, a bluetooth receiver and a last generation FM/DAB+ module.

It is suitable both for constant voltage and low impedance connections of speakers with a maximum power of up to 60W. It features 3 mic inputs and 4 line inputs. The MIC1 input is XLR type and supports +48V phantom power for condenser microphones. It is also endowed with tel paging, 24V power supply and several protection circuits.

MP3 compatible	Yes
Input connectors	XLR + RCA + Jack 6,3mm
Output connectors	Terminals
Line inputs	4
Mic inputs	3
Impedance	4 - 8 - 16 Ohms
Siren & Whistle	No
Constant voltage	70 - 100V compatible
8 Ohm max power	60W
S/N ratio	Line>85dB, Mic >72dB
Frequency response	60Hz - 15 KHz
Voice priority function	Yes, on MIC 1 only
VU METERS	Yes
Phantom Key	Yes
RMS power	30W
Mp3 player	Yes
Tel paging function	Yes
Matrix	No
DC Power	24V
Bluetooth	Ver. 5.0
Color	black
Weight	3,7 kg
Product dimensions	320 x 90 x 210mm
Power supply	110V - 220V





Karma Italiana srl si impegna affinchè le informazioni contenute in questa scheda siano le più precise possibili. Allo scopo di migliorare i propri prodotti, Karma Italiana si riserva il diritto di apportare modifiche ai propri prodotti senza alcun preavviso. Tutti i prodotti Karma sono conformi alle normative vigenti dell'Unione Europea.



