

SCHEDA TECNICA / TECHNICAL SHEET

## **PM 1 Desktop paging microphone**







Desktop paging microphone offering the possibility to manage announcements on 6 zones and compatible with amplifiers mod. PAA 120MZ, PAA 240MZ, PAA 480MZ and PAA 1000MZ.

It can be connected to the amplifier via an RJ-45 cable and features buttons for announcements on individual zones or simultaneously on all zones.

The distance from the amplifier can be extended up to 200m using CAT5/6 network cables. It is possible to connect up to 6 microphones with different priorities.

The gooseneck microphone is 41cm long and ends with a capsule protected by a windscreen sponge cover. The line input on the back is useful to forward a signal to one or more zones as an alternative to the announcement.

Main features:

Gooseneck mic connector

Power supply led indicator

Busyaled indicator

Speaker zone led indicator (1-6)

서한한ZONE selection button 0,9 kg Gadl/tedknoutton

Sall/talk-button 170 x 50 x 152 mm
RJ45 port for cascade connection of other microphones

RJ45 port for connection to an amplifier

Possibilty of connection to an amplifier through cat 5/6 cable

Mic gain control Local AUX in

Karma Italiana srl si impegna affinchè le informazioni contenute in questa scheda siano le più precise possibili. Allo scopo di migliorare i propri prodotti, Karma Italiana si riserva il diritto di apportare modifiche ai propri prodotti senza alcun preavviso. Tutti i prodotti Karma sono conformi alle normative vigenti dell'Unione Europea.



